

IPL Green MDS



Colour: green

Temperature Range: - 25°C + 60°C.

Suitable for:

Applications: Waste Management, Agriculture

Industries: Agriculture, Waste Management

Features

Technical features: PVC hose reinforced with an anti-shock rigid PVC spiral. completely free from phthalates with smooth bore, slightly corrugated outside .

Properties: Particularly suitable to be used even at low temperatures, high mechanical properties, light, flexible, good bending, resistant to torsion, crushing, weather conditions, ageing, ozone, hydrolysis and most chemicals.

Application Fields

Excellent for liquid suction and delivery , particularly suitable to be used on tank trucks thanks to its physical-mechanical features.

For different coil length contact Sales office.

Technical Data

Part Number	Inside Ø	Min. Wall Thickness	Max Wall Thickness	Weight	Working Pressure	Bursting Pressure	Vacuum	Bending	Roll Length	Volume
	mm	mm	mm	g/m	bar	bar	m H2O	mm	m	m ³
NXNF 025.0 000.0	25	2.7	3.0	310	3.3	10	5	110	30	0.085
NX NF 032.0 000.0	31,8	2.8	3.1	400	3.3	10	5	140	30	0.128
NX NF 038.0 000.0	38,1	3.0	3.5	520	3.3	10	5	160	30	0.183
NX NF 052.0 000.0	51.5	3.4	4.2	820	3.3	10	5	200	30	0.297
NX NF 063.0 000.0	63.5	3.5	4.3	1060	3.3	10	5	250	30	0.488
NX NF 076.0 000.0	76.2	3.9	4.9	1400	3.3	10	5	290	30	0.655
NX NF 102.0 000.0	102	4,8	6.0	2280	3.0	9	5	400	30	0.729
NX NF 127.0 000.0	127	5.2	6.5	3040	2.0	6	3	580	20/30	1.130
NX NF 150.0 000.0	151.5	6.2	7.7	4350	2.0	6	3	660	20/30	1.282

Industries

Agriculture

Waste Management